

Specifications

Indoor Model Name			FTNK20AV1K9	FTNK25AV1K9
Outdoor Model Name			RNK20AV1K9	RNK25AV1K9
Nominal Cooling Capacity (T1)*	Btu/hr		17,000	23,000
	W		5,280	7,030
Nominal Cooling Capacity (T3)**	Btu/hr		14,200	18,300
	W		4,180	5,380
Rated EER (T1)*	(Btu/h)/W		11.04	11.21
Rated EER (T3)**	(Btu/h)/W		7.36	7.04
Indoor	Power Supply	V/Ph/Hz	220-240/1/50	
	Air Flow	CFM	594/531/474/422/381	641/614/537/474/418
	Sound Pressure Level	dBA	44/42/39/36/35	48/46/43/39/37
	Height	mm	320	
	Width	mm	1,172	
	Depth	mm	242	
	Net Weight	kg	14	
	Casing	Colour	White	
Outdoor	Power Supply	V/Ph/Hz	220-240/1/50	220-240/1/50
	Sound Pressure Level	dBA	54	
	Height	mm	651	753
	Width	mm	855	
	Depth	mm	328	
	Net Weight	kg	49	57
	Pipe Connection - Liquid	mm	6.35	
	Pipe Connectionn - Gas	mm	12.7	15.88
	Maximum Piping Length	m	35	
	Maximum Piping Elevation	m	15	
	Compressor	Type	Rotary	
	Operating Temperature Range (Min-Max)	°C	19-54	

* T1 : Indoor- 27°C DB / 19°C WB, Outdoor- 35°C DB/24°C WB

** T3 : Indoor- 29°C DB / 19°C WB, Outdoor- 46°C DB/24°C WB