

Specifications

Indoor Model Name		FTNK20AV1KR	FTNK25AV1KR
Outdoor Model Name		RNK20AV1KR	RNK25AV1KR
Nominal Cooling Capacity (T1)*	Btu/hr	18,000	24,000
	W	5,280	7,030
Nominal Cooling Capacity (T3)**	Btu/hr	14,200	18,300
	W	4,180	5,380
Rated EER (T1)*	(Btu/h)/W	11.04	11.21
Rated EER (T3)**	(Btu/h)/W	7.36	7.04
Indoor	Power Supply	V/Ph/Hz	220-240/1/50
	Air Flow	CFM	594/531/474/422/381
	Sound Pressure Level	dBA	44/42/39/36/35
	Height	mm	320
	Width	mm	1,172
	Depth	mm	242
	Net Weight	kg	14
	Casing	Colour	White
Outdoor	Power Supply	V/Ph/Hz	220-240/1/50
	Sound Pressure Level	dBA	54
	Height	mm	651
	Width	mm	855
	Depth	mm	328
	Net Weight	kg	49
	Pipe Connection - Liquid	mm	6.35
	Pipe Connectionn - Gas	mm	12.7
	Maximum Piping Length	m	35
	Maximum Piping Elevation	m	15
	Compressor	Type	Rotary
	Operating Temperature Range (Min-Max)	°C	19-54

* T1 : Indoor- 27°C DB / 19°C WB, Outdoor- 35°C DB/24°C WB

** T3 : Indoor- 29°C DB / 19°C WB, Outdoor- 46°C DB/24°C WB